

Cabling Racks suited for data center and tele- communications providers



Internal dimensions to IEC 297-2 and DIN 41494 Part 1 with addition to DIN-IEC drilling in EIA standard.

- Protection to foreign bodies to IP20; DIN 40050 Part 1 & IEC 529.

- Load carrying capacity 500kg.

RAXXES



RAXXES STANDARD CLOSED RACK

Available Sizes: **20U , 24U, 28U, 33U, 36U, 39U, 42U**

Frame: **19" and 24"**

Depth (outer):**900mm , 1000mm, 1100mm and 1200mm**

Dimensions (outer): **900/1000/1100/1200 mm x 600/800 mm**

Color: **Black, Gray , Blue**

Sizes	Part Numbers	Mounting Frame Size		Depths Available (mm)			
		19"	24"	900	1000	1100	1200
20U	RA20U19X900	yes		yes			
24U	RA24U19X900	yes		yes			
28U	RA28U19X900	yes		yes			
33U	RA33U19X900	yes		yes			
36U	RA36U19X900	yes		yes			
39U	RA39U19X900	yes		yes			
42U	RA42U19X <i>depth</i> *	yes	yes	yes	yes	yes	yes

* please insert your chosen depth for the 42U size rack. e.g. RA42U19X900 for a 900mm depth rack

All of our racks and cabinets are user customizable insuring that you get the best server equipment rack for your needs. Just click on the size of server rack you need, select the options you would like in the cabinet, and which rack mount accessories you need. It's that easy! We will meet your needs and ship it to you - usually within a few days of placing your order with us. Compatible with server manufacturer's equipment including: Compaq, Dell, HP, IBM, Sun, and Intel.

Features:

Frame with top cover

Base frame

Mild steel mounting rails

Removable and lockable side panels

Removable, lockable vented rear door

Removable, lockable glass front door

Cooling fans

Power strip

Castor wheel with adjustable feet

Set of cage nut and mounting screws